

Axle spacing

Number of Axles

	Unpaved 2 Axles	Paved 2 Axles	3 Axles	4 Axles	5 Axles	6 Axles	7 Axles	8 Axles
4	34000	34000						
5	34000	34000						
6	34000	34000						
7	34000	34000						
8	34000	34000	37000 38500					
8 plus	34000	38000	42000					
9	35000	39000	43000					
10	36000	40000	43500	49000				
11			44500	49500				
12			45000	50000				
13			46000	51000				
14			46500	51500	57000			
15			47500	52000	57500			
16			48000	53000	58000			
17			49000	53500	59000			
18			49500	54000	59500			
19			50500	55000	60000			
20			51000	55500	60500	66000	72000	
21			52000	56000	61500	67000	72500	
22			52500	57000	62000	67500	73000	
23			53500	57500	62500	68000	73500	
24			54000	58000	63000	68500	74000	
25			55000	59000	64000	69000	75000	
26			55500	59500	64500	70000	75500	
27			56500	60000	65000	70500	76000	
28			57000	61000	65500	71000	76500	
29			58000	61500	66500	71500	77000	
30			58500	62000	67000	72000	77500	
31			59500	63000	67500	73000	78500	
32			60000	63500	68000	73500	79000	
33				64000	69000	74000	79500	
34				65000	69500	74500	80000	
35				65500	70000	75000	80500	86000
36				66000	70500	76000	81000	86500
37				67000	71500	76500	81500	87000
38				67500	72000	77000	82000	87500
39				68000	72500	77500	82500	88500
40				69000	73000	78000	83500	89000
41				69500	74000	79000	84000	89500
42				70000	74500	79500	84500	90000
43				71000	75000	80000	85000	90500
44				71500	75500	80500	85500	91000
45				72000	76500	81000	86000	91500
46				72500	77000	81500	87000	92500
47				73500	77500	82000	87500	93000
48				74000	78000	83000	88000	93500
49				74500	79000	83500	88500	94000
50				75500	79500	84000	89000	94500
51				76000	80000	84500	89500	95000
52				76500	80500	85000	90500	95500
53				77500	81000	86000	91000	96500
54				78000	81500	86500	91500	97000
55				78500	82500	87000	92000	97500
56				79500	83000	87500	92500	98000
57				80000	83500	88000	93000	98500
58					84000	89000	94000	99000
59					85500	89500	94500	99500
60					86000	90000	95000	100500
61							95500	101000
62							96000	101500
63							96500	102000
64							97000	102500
65								103000
66								103500
67								104500
68								105000
69								105500
70								106000
71								106500
72								107000
73								107500
74								108000

Applies only to vehicles manufactured before August 1, 1991.

Vehicles manufactured on or after August 1, 1991, are limited to 34,000 pounds on 3 axles spaced at 7 or 8 feet.

The Gross Weight Schedule is provided in Minnesota Statute 169.824, Subd. 1

These weights allowed on paved routes only

Two consecutive tandems may carry a gross weight of 34,000 lbs. each, and a total of 68,000 lbs. together, when the centers of the first and last axle of the group are spaced 36 feet or more.

These weights allowed on paved routes only

Weights shown in RED valid only for vehicles operating under the terms of a special transportation permit issued by the proper road authority.