

“Sample”

The following is a typical pole note that calls for angle or straight mount plumbizer for vehicle or pedestrian signal indications on a vertical pole shaft of a mast arm pole standard:

EB STA 172+38, 32' RT  
PA100 POLE FOUNDATION  
TYPE PA100-A-50-D40-9 (DAVIT AT 350 DEG)  
2-SWING AWAY HINGES  
**1-ANGLE MOUNT SIGNAL OVERHEAD AT 0'**  
**2-STRAIGHT MOUNT SIGNALS OVERHEAD**  
**AT 11' AND 23'**  
**2-ANGLE MOUNT SIGNALS AT 90 AND 180 DEG**  
**1-ANGLE MOUNT C. D. PED IND AT 180 DEG**  
1-ONE WAY EVP DETECTOR AND  
CONFIRMATORY LIGHT (PHASES 2+5)  
LUMINAIRE-250W HPS  
1-APS PB AND SIGN (LT ARROW) (PB2-2)  
1-SIGN D-A2 ELM ST W  
1-SIGN R6-1L ONE WAY  
1-SIGN R6-1R ONE WAY  
1-SIGN R9-3A NO PED (FACING POLE 2)  
3" CONDUIT TO HH 8:  
2-12/C #14  
1-4/C #14  
1-3/C #14  
1-3/C #14 LUM  
1-2/C #14  
1-3/C #20  
1-1/C #6 INS. GR.