

Price quote for:	11.0 Exhibit D PRICE SCHEDULE ANTI-ICING	
Vendor Name:	Fortbrand Services, Inc	
Contact Person:	Carlton Braley	
Street Address:	50 Fairchild Court	
P.O. Box:		
City, State, Zip:	Plainview, NY 11803	
Phone #:	516-576-3200	
Toll Free #:		
Fax #:	516-576-3221	
Email Address:	cbraley@fortbrand.com	
Item #	Information Requested	Answer
11.0	Anti-Icing, Make & Model	VAMMAS DTR1000
	Size of Tank & Configuration	1,000 Gallon Tank; poly tank with UV protection
	Tank Baffle Description	
	Manhole Size	16-inch with 10" fill access and cover
	Skid Plate & Tank Strap Description	
	Size Truck Intended For? (Single or Tandem)	Single_____ Tandem____
	Installation Method of Tank? (Backed into or Set on Chassis)	Trailer
	Number of Lanes Standard Boom Covers	4
	Nozzle Description (PVC, SS, Fan or Streamjet?)	Spray tubes are 304 SS tubing
	Nozzle Valve Description (Ball Valve or Proportionally Controlled)	Nozzles spaced 30" apart to give triple overlap coverage. Each boom section is capable of spraying independently
	Boom Spraying Speed (High Speed, Low Speed)	microprocessor located in the cab of the vehicle. The rate of liquid dispersal adjusts with the changes in the vehicle speed to give a constant applied rate on the surface. The liquid control system is infinitely adjustable
	Pump Flow Rate (GPM and PSI)	200-gpm minimum
	Type of Pump	Corrosion-resistant centrifugal pump
	How is Pump Powered? Describe Power Unit.	The axial piston model A10VO is a variable displacement pump with pressure compensator
	Does it include controls?	includes a minimum output of 75cc and 28.5 GPM
	Control Description	system senses ground speed, spray width (number of lanes), and material flow rate. If a change in ground speed or spray width is detected, the control system changes the material flow rate to maintain a constant, pre-selected application rate.
	Is it Ground Speed Orientated?	Yes
	Can it be filled with Sprayer Pump from Control Panel?	Yes_X_ or No_____
	Tank Warranty	1 year
	Control Warranty	1 year

	Pump Warranty	1 year
	Spring Bar & Nozzle Warranty	1 year
	List Volume Discounts	2.5%
	TOTAL PRICE	\$ 72,000.00
	Description	Answer
	Cost per loaded mile for delivery of anti-icing system	\$15.00/ mile
	Starting Point: City, State, Zip:	Richmond, IN
	Body Shop Rate	\$
	Mechanic Shop Rate	\$

Price quote for:	11.0 Exhibit D PRICE SCHEDULE ANTI-ICING	
Vendor Name:	Fortbrand Services, Inc	
Contact Person:	Carlton Braley	
Street Address:	50 Fairchild Court	
P.O. Box:		
City, State, Zip:	Plainview, NY 11803	
Phone #:	516-576-3200	
Toll Free #:		
Fax #:	516-576-3221	
Email Address:	cbraley@fortbrand.com	
Item #	Information Requested	Answer
11.0	Anti-Icing, Make & Model	VAMMAS DTR2000
	Size of Tank & Configuration	2,000 Gallon Tank; poly tank with UV protection.
	Tank Baffle Description	
	Manhole Size	16-inch with 10" fill access and cover
	Skid Plate & Tank Strap Description	
	Size Truck Intended For? (Single or Tandem)	Single_____ Tandem_____
	Installation Method of Tank? (Backed into or Set on Chassis)	Trailer
	Number of Lanes Standard Boom Covers	4
	Nozzle Description (PVC, SS, Fan or Streamjet?)	Spray tubes are 304 SS tubing
	Nozzle Valve Description (Ball Valve or Proportionally Controlled)	Nozzles spaced 30" apart to give triple overlap coverage. Each boom section is capable of spraying independently
	Boom Spraying Speed (High Speed, Low Speed)	Application rate of the deicing fluid is controlled with a microprocessor located in the cab of the vehicle. The rate of liquid dispersal adjusts with the changes in the vehicle speed to give a constant applied rate on the surface. The liquid control system is infinitely adjustable
	Pump Flow Rate (GPM and PSI)	200-gpm minimum
	Type of Pump	Corrosion-resistant centrifugal pump
	How is Pump Powered? Describe Power Unit.	The axial piston model A10VO is a variable displacement pump with pressure compensator
	Does it include controls?	includes a minimum output of 75cc and 28.5 GPM
	Control Description	system senses ground speed, spray width (number of lanes), and material flow rate. If a change in ground speed or spray width is detected, the control system changes the material flow rate to maintain a constant, pre-selected application rate.
	Is it Ground Speed Orientated?	Yes
	Can it be filled with Sprayer Pump from Control Panel?	Yes_X_ or No_____
	Tank Warranty	1 year

Control Warranty	1 year
Pump Warranty	1 year
Spring Bar & Nozzle Warranty	1 year
List Volume Discounts	2.5%
TOTAL PRICE	\$ 121,984.00
Description	Answer
Cost per loaded mile for delivery of anti-icing system	\$15.00/ mile
Starting Point: City, State, Zip:	Richmond, IN
Body Shop Rate	\$
Mechanic Shop Rate	\$