

Price quote for:		6.0 NON MnDOT PRICE SCHEDULE - FRONT SNOW PLOW
Vendor Name:	<b>Universal Truck Equipment Inc.</b>	
Contact Person:	<b>Donnie Bjorge</b>	
Street Address:	<b>N15921 Schubert Rd.</b>	
P.O. Box:		
City, State, Zip:	<b>Galesville, WI 54630</b>	
Phone #:	<b>608-539-4600</b>	
Toll Free #:		
Fax #:	<b>608-539-4800</b>	
Email Address:	<b>donnie@universaltruckequipment.com</b>	
	Information Requested	Answer
	Plow Type ( one way, reversable, high wing, v plow, etc)	
6.00	R.H. Snowplow, Make & Model	<b>Universal - OWUTA-11-33-56L (R.H.) One Way Snow Plow - 11' plow length, Loop Hitch is Std. (see options for other available plow portion hitches).</b>
6.00	L.H. Snowplow, Make & Model	<b>N/A</b>
	Nose Height	<b>33" plow height at inlet end</b>
	Discharge Height	<b>56" plow height at outlet end</b>
	Plow Throat Depth from Vertical to the Deepest Point	<b>25"</b>
	Plowing Angle	<b>35 Degrees</b>
	Moldboard Thickness & Type of Steel	<b>3/16" thick, grade 50 Hi-tensile steel. Plow is fully welded</b>
	Type, Size, and Number of Vertical Reinforcement Ribs	<b>Seven 1/2" flame cut ribs (counting the endplate), 11' plow. Eight 1/2" flame cut ribs (counting the endplate), 12' plow. Ribs are 100% fully welded.</b>
	Adjustable Cutting Edge Angles to Pavement Measured from Roadway Surface through Perpendicular Back Toward Truck	<b>15 degrees to 30 degrees</b>
	State the Number of Hook-up Points from Moldboard to Frame	<b>Six (6)</b>
	Type and Size of Reinforcement of Frog at either end	<b>3/4" x 4" x 4" lower angle, fully gusseted (carbide punched)</b>
	Type of Left Side Nose	<b>3/16" grade 50 plate (Bolt-On)</b>
	Size and Type of Reinforced Snow Flap	<b>3-ply, 1/2" thick x 12" wide</b>
	Type and Size of Push Frame	<b>Heavy duty push frame constructed with 3/8" x 4" x 4" x 117" square tubing</b>
	Carbide Cutting Edge (AASHTO Punched) Size	<b>5/8" x 8" x (length of plow) steel cutting edge is standard (see options for carbide)</b>

	Distance Beyond Vertical that Nose Snow Deflectors Integrate with Moldboard Extends	<b>22"</b>	
	Distance beyond Vertical that Discharge Snow Deflectors Integral with Moldboard Extends	<b>41"</b>	
	Size of Adjustable Snow Shoes	<b>None - See Options Includes adjustable parking stand</b>	
	Weight of Plow (less Hitch and Hydraulics)	<b>2,050 lbs.</b>	
	Type and Number of re-settable HD Compression Spring Trip Mechanisms	<b>Four (4) heavy duty adjustable moldboard trip springs, extension type, adjustable with hand tools, made of 9/16" wire.</b>	
	Painting System with Type of Paint	<b>Primed &amp; Painted Std. Black (see options for different colors)</b>	
	Warranty Information	<b>One Year Warranty, parts and labor</b>	
	Volume Discounts	<b>N/A</b>	
	<b>TOTAL PRICE:</b>	<b>\$</b>	<b>11,415.00</b>
	Front Plow Options		
6.01	12' plow length in lieu of 11' (33" inlet & 60" discharge)	\$	402.71
6.02	13' plow length in lieu of 11' (31" inlet & 62" discharge)	\$	1,323.02
6.03	Std. UTE Orange painted plow in lieu of std. black (All Plow Models & Sizes) (#IG4241040)	\$	173.97
6.04	Std. UTE Yellow painted plow in lieu of std. black (All Plow Models & Sizes) (#4421)	\$	517.61
6.05	Std. UTE Red painted plow in lieu of std. black (All Plow Models & Sizes) (#2303)	\$	644.33
6.06	Plow portion of 29" Husting hitch in lieu of Loop Hitch	\$	1,600.09
6.07	Plow portion of 34" Husting hitch in lieu of Loop Hitch	\$	1,857.82
6.08	Roller Kit for 29" or 34" Husting hitch, installed on plow only	\$	667.96
6.09	Plow portion of Snap Link hitch in lieu of Loop Hitch	\$	845.15
6.10	Plow portion of Universal Pin hitch (Falls #46) in lieu of Loop Hitch	\$	201.89
6.11	Level lift assy. for Universal Pin hitch	\$	300.69
6.12	Plow end markers, red cable type, 27", installed (set)	\$	105.24
6.13	Adjustable mushroom type shoes- std. pad, 12" round x 2" thick (installed with standard shoe brackets)	\$	1,711.77
6.14	Adjustable mushroom type shoes- Ni-Hard pad, 12" round x 2" thick (installed with standard shoe brackets)	\$	2,424.83
6.15	Adjustable shoes- Flat type shoe pad (installed with standard shoe brackets)	\$	1,704.25

6.16	Curb shoe, (2" cold rolled round), installed (each)	\$	182.56
6.17	Plow cutting edge shoe, installed (each)	\$	300.69
6.18	Trip cutting edge, one piece or split, in lieu of moldboard trip	\$	1,804.12
6.19	Individually replaceable trip edge springs ilo standard	\$	665.81
6.20	3/4" x 6" carbide cutting edge with cover blade in lieu of std. (per ft.)	\$	106.31
6.21	Sabre Shielded Carbide cutting edge blades 3/4" x 6" ilo std. ("No" cover blade required) (per ft.)	\$	148.20
6.22	Flex Pro (Joma) cutting edge blades 3/4" x 6" ilo std. (Includes cover bar) (per ft.)	\$	177.19
6.23	Flex Pro (Joma) backer blades for additional support (per ft.)	\$	21.48
6.24	Power reverse plow in lieu of fixed angle, 2) 4" x 19" power reversing cylinders with A-frame (with Loop or Snap Link hitch)	\$	2,384.02
6.25	Power reverse plow in lieu of fixed angle, 2) 4" x 19" power reversing cylinders with A-frame (with Husting Hitch)	\$	2,845.79
6.26	Mailbox/Guard rail corner cut (per side)	\$	515.46
6.27	Three piece trip cutting edge in lieu of std. 2-piece trip cutting edge	\$	208.33
6.28	UTE Frog Saver- Installed (helps prevent wearing into the lower angle) (Each)	\$	294.24
6.29	3/4" x 4" x 4" lower trip edge angle in lieu of std. 1/2" x 3" x 4"	\$	177.19
6.30	1/2" Stucchi Multifaster coupler with parking station- installed (coupling under pressure)	\$	1,575.39
	applicable):	\$	<b>5.60</b>
	Delivery Starting Point City, State, & Zip:		
	Body Shop Rate	\$	<b>120.00</b>
	Mechanic Shop Rate	\$	<b>120.00</b>

Price quote for:	<b>6.0 NON MnDOT PRICE SCHEDULE - FRONT SNOW PLOW</b>	
Vendor Name:	<b>Universal Truck Equipment Inc.</b>	
Contact Person:	<b>Donnie Bjorge</b>	
Street Address:	<b>N15921 Schubert Rd.</b>	
P.O. Box:		
City, State, Zip:	<b>Galesville, WI 54630</b>	
Phone #:	<b>608-539-4600</b>	
Toll Free #:		
Fax #:	<b>608-539-4800</b>	
Email Address:	<b>donnie@universaltruckequipment.com</b>	
	<b>Information Requested</b>	<b>Answer</b>
	<b>Plow Type ( one way, reversable, high wing, v plow, etc)</b>	
6.00	R.H. Snowplow, Make & Model	<b>Universal - OWUTA-11-30-50L (R.H.) One Way Snow Plow - 11' plow length, Loop Hitch is Std. (see options for other available plow portion hitches).</b>
6.00	L.H. Snowplow, Make & Model	<b>N/A</b>
	Nose Height	<b>30" plow height at inlet end</b>
	Discharge Height	<b>50" plow height at outlet end</b>
	Plow Throat Depth from Vertical to the Deepest Point	<b>25"</b>
	Plowing Angle	<b>35 degrees</b>
	Moldboard Thickness & Type of Steel	<b>10ga. moldboard thickness, grade 50 Hi-tensile steel. Plow is fully welded</b>
	Type, Size, and Number of Vertical Reinforcement Ribs	<b>Seven 1/2" flame cut ribs (counting the endplate), 11' plow. Eight 1/2" flame cut ribs (counting the endplate), 12' plow. Ribs are 100% fully welded.</b>
	Adjustable Cutting Edge Angles to Pavement Measured from Roadway Surface through Perpendicular Back Toward Truck	<b>15 degrees to 30 degrees</b>
	State the Number of Hook-up Points from Moldboard to Frame	<b>Six (6)</b>
	Type and Size of Reinforcement of Frog at either end	<b>3/4" x 4" x 4" lower angle, fully gusseted (carbide punched)</b>
	Type of Left Side Nose	<b>3/16" grade 50 plate (Bolt-On)</b>
	Size and Type of Reinforced Snow Flap	<b>3-ply, 1/2" thick x 12" wide</b>
	Type and Size of Push Frame	<b>Heavy duty push frame constructed with 3/8" x 4" x 4" x 117" square tubing</b>
	Carbide Cutting Edge (AASHTO Punched) Size	<b>5/8" x 8" x (length of plow) steel cutting edge is standard (see options for carbide)</b>
	Distance Beyond Vertical that Nose Snow Deflectors Integrate with Moldboard Extends	<b>22"</b>
	Distance beyond Vertical that Discharge Snow Deflectors Integral with Moldboard Extends	<b>41"</b>
	Size of Adjustable Snow Shoes	<b>None - See Options Includes adjustable parking stand</b>
	Weight of Plow (less Hitch and Hydraulics)	<b>1,680 lbs.</b>

	Type and Number of re-settable HD Compression Spring Trip Mechanisms	<b>Four (4) heavy duty adjustable moldboard trip springs, extension type, adjustable with hand tools, made of 9/16" wire.</b>
	Painting System with Type of Paint	<b>Primed &amp; Painted Std. Black (see options for different colors)</b>
	Warranty Information	<b>One Year Warranty, parts and labor</b>
	Volume Discounts	<b>N/A</b>
	<b>TOTAL PRICE:</b>	<b>\$ 10,325.00</b>
	Front Plow Options	
6.01	12' plow length in lieu of 11' (30" inlet & 54" discharge)	\$ 402.71
6.02	13' plow length in lieu of 11' (28" inlet & 57" discharge)	\$ 1,323.02
6.03	Std. UTE Orange painted plow in lieu of std. black (All Plow Models & Sizes) (#IG4241040)	\$ 173.97
6.04	Std. UTE Yellow painted plow in lieu of std. black (All Plow Models & Sizes) (#4421)	\$ 517.61
6.05	Std. UTE Red painted plow in lieu of std. black (All Plow Models & Sizes) (#2303)	\$ 644.33
6.06	Plow portion of 29" Husting hitch in lieu of Loop Hitch	\$ 1,600.09
6.07	Plow portion of 34" Husting hitch in lieu of Loop Hitch	\$ 1,857.82
6.08	Roller Kit for 29" or 34" Husting hitch, installed on plow only	\$ 667.96
6.09	Plow portion of Snap Link hitch in lieu of Loop Hitch	\$ 845.15
6.10	Plow portion of Universal Pin hitch (Falls #46) in lieu of Loop Hitch	\$ 201.89
6.11	Level lift assy. for Universal Pin hitch	\$ 300.69
6.12	Plow end markers, red cable type, 27", installed (set)	\$ 105.24
6.13	Adjustable mushroom type shoes- std. pad, 12" round x 2" thick (installed with standard shoe brackets)	\$ 1,711.77
6.14	Adjustable mushroom type shoes- Ni-Hard pad, 12" round x 2" thick (installed with standard shoe brackets)	\$ 2,424.83
6.15	Adjustable shoes- Flat type shoe pad (installed with standard shoe brackets)	\$ 1,704.25
6.16	Curb shoe, (2" cold rolled round), installed (each)	\$ 182.56
6.17	Plow cutting edge shoe, installed (each)	\$ 300.69
6.18	Trip cutting edge, one piece or split, in lieu of moldboard trip	\$ 1,804.12
6.19	Individually replaceable trip edge springs ilo standard	\$ 665.81
6.20	3/4" x 6" carbide cutting edge with cover blade in lieu of std. (per ft.)	\$ 106.31
6.21	ft.)	\$ 148.20
6.22	Flex Pro (Joma) cutting edge blades 3/4" x 6" ilo std. (Includes cover bar) (per ft.)	\$ 177.19
6.23	Flex Pro (Joma) backer blades for additional support (per ft.)	\$ 21.48
6.24	Power reverse plow in lieu of fixed angle, 2) 4" x 19" power reversing cylinders with A-frame (with Loop or Snap Link hitch)	\$ 2,384.02
6.25	Power reverse plow in lieu of fixed angle, 2) 4" x 19" power reversing cylinders with A-frame (with Husting Hitch)	\$ 2,845.79

6.26	Mailbox/Guard rail corner cut (per side)	\$	515.46
6.27	Three piece trip cutting edge in lieu of std. 2-piece trip cutting edge	\$	208.33
6.28	UTE Frog Saver- Installed (helps prevent wearing into the lower angle) (Each)	\$	294.24
6.29	3/4" x 4" x 4" lower trip edge angle in lieu of std. 1/2" x 3" x 4"	\$	177.19
6.30	1/2" Stucchi Multifaster coupler with parking station- installed (coupling under pressure)	\$	1,575.39
	Cost per loaded mile for pickup and or delivery of vehicle (if applicable):	\$	<b>5.60</b>
	Delivery Starting Point City, State, & Zip:	<b>N15921 Schubert Rd., Galesville, WI 54630</b>	
	Body Shop Rate	\$	<b>120.00</b>
	Mechanic Shop Rate	\$	<b>120.00</b>

Price quote for:	<b>6.0 NON MnDOT PRICE SCHEDULE - FRONT SNOW PLOW</b>	
Vendor Name:	<b>Universal Truck Equipment Inc.</b>	
Contact Person:	<b>Donnie Bjorge</b>	
Street Address:	<b>N15921 Schubert Rd.</b>	
P.O. Box:		
City, State, Zip:	<b>Galesville, WI 54630</b>	
Phone #:	<b>608-539-4600</b>	
Toll Free #:		
Fax #:	<b>608-539-4800</b>	
Email Address:	<b>donnie@universaltruckequipment.com</b>	
	<b>Information Requested</b>	<b>Answer</b>
	<b>Plow Type ( one way, reversable, high wing, v plow, etc)</b>	
6.00	R.H. Snowplow, Make & Model	<b>Universal - OWCST-11-33-56L (R.H.) One Way Snow Plow - 11' plow length, Loop Hitch is Std. (see options for other available plow portion hitches).</b>
6.00	L.H. Snowplow, Make & Model	<b>N/A</b>
	Nose Height	<b>33" plow height at inlet end</b>
	Discharge Height	<b>56" plow height at outlet end</b>
	Plow Throat Depth from Vertical to the Deepest Point	<b>25"</b>
	Plowing Angle	<b>35 degrees</b>
	Moldboard Thickness & Type of Steel	<b>3/16" thick, grade 50 Hi-tensile steel. Plow is fully welded</b>
	Type, Size, and Number of Vertical Reinforcement Ribs	<b>flame cut ribs (counting the endplate), 12' plow. Ribs are 100% fully welded.</b>
	Adjustable Cutting Edge Angles to Pavement Measured from Roadway Surface through Perpendicular Back Toward Truck	<b>15 degrees to 30 degrees</b>
	State the Number of Hook-up Points from Moldboard to Frame	<b>Six (6)</b>
	Type and Size of Reinforcement of Frog at either end	<b>3/4" x 4" x 4" lower angle, fully gusseted (carbide punched)</b>
	Type of Left Side Nose	<b>3/16" grade 50 plate (Bolt-On)</b>
	Size and Type of Reinforced Snow Flap	<b>3-ply, 1/2" thick x 12" wide</b>
	Type and Size of Push Frame	<b>Heavy duty push frame constructed with 3/8" x 4" x 4" x 117" square tubing</b>
	Carbide Cutting Edge (AASHTO Punched) Size	<b>5/8" x 8" x (length of plow) steel cutting edge is standard (see options for carbide)</b>
	Distance Beyond Vertical that Nose Snow Deflectors Integrate with Moldboard Extends	<b>22"</b>
	Distance beyond Vertical that Discharge Snow Deflectors Integral with Moldboard Extends	<b>41"</b>
	Size of Adjustable Snow Shoes	<b>None - See Options Includes adjustable parking stand</b>
	Weight of Plow (less Hitch and Hydraulics)	<b>2,005 lbs.</b>
	Type and Number of re-settable HD Compression Spring Trip Mechanisms	<b>Two (2) heavy duty moldboard trip springs, compression type, made of 9/16" wire</b>
	Painting System with Type of Paint	<b>Primed &amp; Painted Std. Black (see options for different colors)</b>
	Warranty Information	<b>One Year Warranty, parts and labor</b>
	on	<b>N/A</b>
	<b>TOTAL PRICE:</b>	<b>\$ 10,234.00</b>

Front Plow Options		
6.01	12' plow length in lieu of 11' (33" inlet & 60" discharge)	\$ 402.71
6.02	13' plow length in lieu of 11' (31" inlet & 62" discharge)	\$ 1,323.02
6.03	Std. UTE Orange painted plow in lieu of std. black (All Plow Models & Sizes) (#G4241040)	\$ 173.97
6.04	(#4421)	\$ 517.61
6.05	Std. UTE Red painted plow in lieu of std. black (All Plow Models & Sizes) (#2303)	\$ 644.33
6.06	Plow portion of 29" Hustling hitch in lieu of Loop Hitch	\$ 1,600.09
6.07	Plow portion of 34" Hustling hitch in lieu of Loop Hitch	\$ 1,857.82
6.08	Roller Kit for 29" or 34" Hustling hitch, installed on plow only	\$ 667.96
6.09	Plow portion of Snap Link hitch in lieu of Loop Hitch	\$ 845.15
6.10	Plow portion of Universal Pin hitch (Falls #46) in lieu of Loop Hitch	\$ 201.89
6.11	Level lift assy. for Universal Pin hitch	\$ 300.69
6.12	Plow end markers, red cable type, 27", installed (set)	\$ 105.24
6.13	Adjustable mushroom type shoes- std. pad, 12" round x 2" thick (installed with standard shoe brackets)	\$ 1,711.77
6.14	Adjustable mushroom type shoes- Ni-Hard pad, 12" round x 2" thick (installed with standard shoe brackets)	\$ 2,424.83
6.15	Adjustable shoes- Flat type shoe pad (installed with standard shoe brackets)	\$ 1,704.25
6.16	Curb shoe, (2" cold rolled round), installed (each)	\$ 182.56
6.17	Plow cutting edge shoe, installed (each)	\$ 300.69
6.18	Trip cutting edge, one piece or split, in lieu of moldboard trip	\$ 1,804.12
6.19	Individually replaceable trip edge springs ilo standard	\$ 665.81
6.20	3/4" x 6" carbide cutting edge with cover blade in lieu of std. (per ft.)	\$ 106.31
6.21	Sabre Shielded Carbide cutting edge blades 3/4" x 6" ilo std. ("No" cover blade required) (per ft.)	\$ 148.20
6.22	ft.)	\$ 177.19
6.23	Flex Pro (Joma) backer blades for additional support (per ft.)	\$ 21.48
6.24	Power reverse plow in lieu of fixed angle, 2) 4" x 10" power reversing cylinders with A-frame (with Loop or Snap Link hitch)	\$ 2,384.02
6.25	Power reverse plow in lieu of fixed angle, 2) 4" x 10" power reversing cylinders with A-frame (with Hustling Hitch)	\$ 2,845.79
6.26	Mailbox/Guard rail corner cut (per side)	\$ 515.46
6.27	Three piece trip cutting edge in lieu of std. 2-piece trip cutting edge	\$ 208.33
6.28	UTE Frog Saver- Installed (helps prevent wearing into the lower angle) (Each)	\$ 294.24
6.29	3/4" x 4" x 4" lower trip edge angle in lieu of std. 1/2" x 3" x 4"	\$ 177.19
6.30	1/2" Stucchi Multifaster coupler with parking station- installed (coupling under pressure)	\$ 1,575.39
	Cost per loaded mile for pickup and or delivery of vehicle (if applicable):	\$ 5.60
	Delivery Starting Point City, State, & Zip:	N15921 Schubert Rd., Galesville, WI 54630
	Body Shop Rate	\$ 120.00
	Mechanic Shop Rate	\$ 120.00



Price quote for:	<b>6.0 NON MnDOT PRICE SCHEDULE - FRONT SNOW PLOW</b>	
Name:	<b>Universal Truck Equipment Inc.</b>	
Contact Person:	<b>Donnie Bjorge</b>	
Street Address:	<b>N15921 Schubert Rd.</b>	
P.O. Box:		
City, State, Zip:	<b>Galesville, WI 54630</b>	
Phone #:	<b>608-539-4600</b>	
Toll Free #:		
Fax #:	<b>608-539-4800</b>	
Email Address:	<b>donnie@universaltruckequipment.com</b>	
	Information Requested	Answer
	Plow Type ( one way, reversable, high wing, v plow, etc)	
6.00	R.H. Snowplow, Make & Model	<b>Universal - OWCST-11-30-50L (R.H.) One Way Snow Plow - 11' plow length, Loop Hitch is Std. (see options for other available plow portion hitches).</b>
6.00	L.H. Snowplow, Make & Model	<b>N/A</b>
	Nose Height	<b>30" plow height at inlet end</b>
	Discharge Height	<b>50" plow height at outlet end</b>
	Plow Throat Depth from Vertical to the Deepest Point	<b>25"</b>
	Plowing Angle	<b>35 degrees</b>
	Moldboard Thickness & Type of Steel	<b>10ga. moldboard thickness, grade 50 Hi-tensile steel. Plow is fully welded</b>
	Type, Size, and Number of Vertical Reinforcement Ribs	<b>Seven 1/2" flame cut ribs (counting the endplate), 11' plow. Eight 1/2" flame cut ribs (counting the endplate), 12' plow. Ribs are 100% fully welded.</b>
	Adjustable Cutting Edge Angles to Pavement Measured from Roadway Surface through Perpendicular Back Toward Truck	<b>15 degrees to 30 degrees</b>
	State the Number of Hook-up Points from Moldboard to Frame	<b>Six (6)</b>
	Type and Size of Reinforcement of Frog at either end	<b>3/4" x 4" x 4" lower angle, fully gusseted (carbide punched)</b>
	Type of Left Side Nose	<b>3/16" grade 50 plate (Bolt-On)</b>
	Size and Type of Reinforced Snow Flap	<b>3-ply, 1/2" thick x 12" wide</b>
	Type and Size of Push Frame	<b>Heavy duty push frame constructed with 3/8" x 4" x 4" x 117" square tubing</b>
	Carbide Cutting Edge (AASHTO Punched) Size	<b>5/8" x 8" x (length of plow) steel cutting edge is standard (see options for carbide)</b>
	Distance Beyond Vertical that Nose Snow Deflectors Integrate with Moldboard Extends	<b>22"</b>
	Distance beyond Vertical that Discharge Snow Deflectors Integral with Moldboard Extends	<b>41"</b>
	Size of Adjustable Snow Shoes	<b>stand</b>

	Weight of Plow (less Hitch and Hydraulics)	<b>2,005 lbs.</b>
	Type and Number of re-settable HD Compression Spring Trip Mechanisms	<b>Two (2) heavy duty moldboard trip springs, compression type, made of 9/16" wire</b>
	Painting System with Type of Paint	<b>Primed &amp; Painted Std. Black (see options for different colors)</b>
	Warranty Information	<b>One Year Warranty, parts and labor</b>
	Volume Discounts	<b>N/A</b>
	<b>TOTAL PRICE:</b>	<b>\$ 9,257.00</b>
	Front Plow Options	
6.01	12' plow length in lieu of 11' (30" inlet & 54" discharge)	\$ 402.71
6.02	13' plow length in lieu of 11' (28" inlet & 57" discharge)	\$ 1,323.02
6.03	Std. UTE Orange painted plow in lieu of std. black (All Plow Models & Sizes) (#IG4241040)	\$ 173.97
6.04	Std. UTE Yellow painted plow in lieu of std. black (All Plow Models & Sizes) (#4421)	\$ 517.61
6.05	Std. UTE Red painted plow in lieu of std. black (All Plow Models & Sizes) (#2303)	\$ 644.33
6.06	Plow portion of 29" Husting hitch in lieu of Loop Hitch	\$ 1,600.09
6.07	Plow portion of 34" Husting hitch in lieu of Loop Hitch	\$ 1,857.82
6.08	Roller Kit for 29" or 34" Husting hitch, installed on plow only	\$ 667.96
6.09	Plow portion of Snap Link hitch in lieu of Loop Hitch	\$ 845.15
6.10	Plow portion of Universal Pin hitch (Falls #46) in lieu of Loop Hitch	\$ 201.89
6.11	Level lift assy. for Universal Pin hitch	\$ 300.69
6.12	Plow end markers, red cable type, 27", installed (set)	\$ 105.24
6.13	Adjustable mushroom type shoes- std. pad, 12" round x 2" thick (installed with standard shoe brackets)	\$ 1,711.77
6.14	Adjustable mushroom type shoes- Ni-Hard pad, 12" round x 2" thick (installed with standard shoe brackets)	\$ 2,424.83
6.15	Adjustable shoes- Flat type shoe pad (installed with standard shoe brackets)	\$ 1,704.25
6.16	Curb shoe, (2" cold rolled round), installed (each)	\$ 182.56
6.17	Plow cutting edge shoe, installed (each)	\$ 300.69
6.18	Trip cutting edge, one piece or split, in lieu of moldboard trip	\$ 1,804.12
6.19	Individually replaceable trip edge springs ilo standard	\$ 665.81
6.20	3/4" x 6" carbide cutting edge with cover blade in lieu of std. (per ft.)	\$ 106.31
6.21	ft.)	\$ 148.20
6.22	Flex Pro (Joma) cutting edge blades 3/4" x 6" ilo std. (Includes cover bar) (per ft.)	\$ 177.19
6.23	Flex Pro (Joma) backer blades for additional support (per ft.)	\$ 21.48
6.24	Power reverse plow in lieu of fixed angle, 2) 4" x 19" power reversing cylinders with A-frame (with Loop or Snap Link hitch)	\$ 2,384.02
6.25	Power reverse plow in lieu of fixed angle, 2) 4" x 19" power reversing cylinders with A-frame (with Husting Hitch)	\$ 2,845.79
6.26	Mailbox/Guard rail corner cut (per side)	\$ 515.46

6.27	Three piece trip cutting edge in lieu of std. 2-piece trip cutting edge	\$	208.33
6.28	UTE Frog Saver- Installed (helps prevent wearing into the lower angle) (Each)	\$	294.24
6.29	3/4" x 4" x 4" lower trip edge angle in lieu of std. 1/2" x 3" x 4"	\$	177.19
6.30	1/2" Stucchi Multifaster coupler with parking station- installed (coupling under pressure)	\$	1,575.39
			.
	Cost per loaded mile for pickup and or delivery of vehicle (if applicable):	\$	5.60
	Delivery Starting Point City, State, & Zip:	<b>N15921 Schubert Rd., Galesville, WI 54630</b>	
	Body Shop Rate	\$	120.00
	Mechanic Shop Rate	\$	120.00

Price quote for:		6.0 NON MnDOT PRICE SCHEDULE - FRONT SNOW PLOW
Vendor Name:	Universal Truck Equipment Inc.	
Contact Person:	Donnie Bjorge	
Street Address:	N15921 Schubert Rd.	
P.O. Box:		
City, State, Zip:	Galesville, WI 54630	
Phone #:	608-539-4600	
Toll Free #:		
Fax #:	608-539-4800	
Email Address:	donnie@universaltruckequipment.com	
	Information Requested	Answer
	Plow Type (one way, reversable, high wing, v plow, etc)	
6.00	Two-Way Reversible Snow Plow - Make and Model	Universal BH-11-43L two way power reversible snow plow, moldboard trip type, 11' plow length. Note: plow portion of loop hitch is standard (see options for other plow hitches).
6.00	Moldboard Height	43" (measured with 6" cutting edge)
	Moldboard Smoothed Rolled Design include Radius.	Multiple radius's 15 to 20
	Discharge Height	43" (measured with 6" cutting edge)
	Plow Throat depth from vertical to deepest point in.	14-1/2"
	Moldboard thickness & type of steel	10ga. moldboard thickness, grade 50 Hi-tensile steel. Plow is fully welded.
	Type, size and number of vertical reinforcement ribs.	Six (6) 1/2" flame cut ribs, ribs are 100% fully welded
	Adjustable cutting edge angles to pavement measured from roadway surface through perpendicular back toward truck.	Fixed angle is 21 degrees, no adjustment
	State number of hook up points from moldboard to frame.	Four (4) (optional heavy duty push frame has six)
	Type and size of reinforcement of frog at either end.	3/4" x 4" x 4" lower angle, fully gusseted (carbide punched)
	Type and size of circle frame	One (1) 4" x 13" reversing cylinder with 2"Nitrided rod mounted in front of pivot point to give the cylinder a 3:1 mechanical advantage for reversing the plow, constructed with 8" ship and car channel.
	Size of double acting reversing cylinders.	One (1) 4" x 13" reversing cylinder w/ brass bushing and grease zerk at live end of cylinder for extended wear.
	Size and type of reinforced snow flap	3-ply, 1/2" thick x 12" wide
	Type and size of push frame	Push frame is constructed with 1/2" thick steel
	Carbide cutting Edge (AASHTO punched) size.	5/8" x 8" x (length of plow) steel cutting edge is standard (see options for carbide)
	Distance beyond vertical that snow deflectors integral with moldboard extends.	28"
	Size of Adjustable Snow Shoes	None - See Options Includes adjustable parking stand
	Weight of plow (less hitch and hydraulics)	2,070 lbs.
	Type and number of resettable HD compression spring trip mechanisms.	Four (4) heavy duty moldboard trip springs, compression type, made of 9/16" wire
	Painting system with type of paint	Primed & Painted Std. Black (See options for different colors)
	Warranty Information	One Year Warranty, parts and labor
	Volume Discounts	N/A
	<b>TOTAL PRICE:</b>	<b>\$ 10,696.00</b>

Front Plow Options		
6.01	12' plow length in lieu of 11'	\$ 263.10
6.02	48" plow height in lieu of 43" (requires optional HDP- must add HDP option)	\$ 641.11
6.03	Std. UTE Orange painted plow in lieu of std. black (All Plow Models & Sizes) (#IG4241040)	\$ 173.97
6.04	Std. UTE Yellow painted plow in lieu of std. black (All Plow Models & Sizes) (#4421)	\$ 517.61
6.05	Std. UTE Red painted plow in lieu of std. black (All Plow Models & Sizes) (#2303)	\$ 644.33
6.06	Plow end markers, red cable type, 27", installed (set)	\$ 105.24
6.07	Adjustable mushroom type shoes- std. pad, 12" round x 2" thick (installed with standard shoe brackets)	\$ 1,711.77
6.08	Adjustable mushroom type shoes- Ni-Hard pad, 12" round x 2" thick (installed with standard shoe brackets)	\$ 2,424.83
6.09	Adjustable shoes- Flat type shoe pad (installed with standard shoe brackets)	\$ 1,704.25
6.10	Curb shoe, (2" cold rolled round), installed (each)	\$ 182.56
6.11	Plow cutting edge shoe, installed (each)	\$ 300.69
6.12	Trip cutting edge, one piece or split, in lieu of moldboard trip	\$ 1,804.12
6.13	Moldboard trip/trip edge combo, in lieu of moldboard trip only	\$ 2,991.84
6.14	Individually replaceable trip edge springs ilo standard	\$ 665.81
6.15	3/4" x 6" carbide cutting edge with cover blade in lieu of std. (per ft.)	\$ 106.31
6.16	Sabre Shielded Carbide cutting edge blades 3/4" x 6" ilo std. ("No" cover blade required) (per ft.)	\$ 148.20
6.17	Flex Pro (Joma) cutting edge blades 3/4" x 6" ilo std. (Includes cover bar) (per ft.)	\$ 177.19
6.18	Flex Pro (Joma) backer blades for additional support (per ft.)	\$ 21.48
6.19	(HDP) Heavy Duty push frame constructed with 1/2" x 4" x 8" x 112" angle eight 1/2" ribs, fully welded, six main hinge points with the furthest hinge point extending about 14" from the end of the plow, in lieu of standard	\$ 1,000.86
6.20	BHW model has the same specs as standard BH. The BHW has a larger more finished off curl (bigger belly) and little more laid back cutting edge. This design helps to throw the snow better. Plow height is 46". (w/ 6" cutting edge) (NO TRIP CUTTING EDGE AVAILABLE ON THIS MODEL)	\$ 413.45
6.21	3/8" Stucchi Multifaster coupler with parking station- installed (coupling under pressure)	\$ 1,277.92
6.22	Plow portion of Snap Link hitch in lieu of Loop hitch	\$ 845.15
6.23	Plow portion of Universal Pin hitch (Falls #46) in lieu of Loop hitch	\$ 201.89
6.24	Level lift assy. for Universal Pin hitch	\$ 300.69
6.25	40" plow height w/ four extension trip springs in lieu of 43" height (deduct)	\$ (344.72)
6.26	Mailbox/Guard rail corner cut (per side)	\$ 451.03
6.27	Three piece trip cutting edge in lieu of std. 2-piece trip cutting edge	\$ 208.33
6.28	UTE Frog Saver- Installed (helps prevent wearing into the lower angle) (Each)	\$ 294.24
6.29	3/4" x 4" x 4" lower trip edge angle in lieu of std. 1/2" x 3" x 4"	\$ 177.19
6.30	3/16" moldboard thickness in lieu of std. 10ga.	\$ 429.55
	Cost per loaded mile for pickup and or delivery of vehicle (if applicable):	\$ 5.60
	Delivery Starting Point City, State, & Zip:	N15921 Schubert Rd., Galesville, WI 54630
	Body Shop Rate	\$ 120.00
	Mechanic Shop Rate	\$ 120.00

Price quote for:	<b>6.0 NON MnDOT PRICE SCHEDULE - FRONT SNOW PLOW</b>	
Vendor Name:	<b>Universal Truck Equipment Inc.</b>	
Contact Person:	<b>Donnie Bjorge</b>	
Street Address:	<b>N15921 Schubert Rd.</b>	
P.O. Box:		
City, State, Zip:	<b>Galesville, WI 54630</b>	
Phone #:	<b>608-539-4600</b>	
Toll Free #:		
Fax #:	<b>608-539-4800</b>	
Email Address:	<b>donnie@universaltruckequipment.com</b>	
	<b>Information Requested</b>	<b>Answer</b>
	Plow Type ( one way, reversable, high wing, v plow, etc)	
6.00	Two-Way Reversible Snow Plow - Make and Model	<b>Universal UTA-11-43L two way power reversible snow plow, moldboard trip type, 11' plow length. Note: plow portion of Loop hitch is standard (see options for other plow hitches).</b>
6.00	Moldboard Height	<b>43" (measured with 6" cutting edge)</b>
	Moldboard Smoothed Rolled Design include Radius.	<b>Multiple radius's 15 to 20</b>
	Discharge Height	<b>43" (measured with 6" cutting edge)</b>
	Plow Throat depth from vertical to deepest point in.	<b>14-1/2"</b>
	Moldboard thickness & type of steel	<b>10ga. moldboard thickness, grade 50 Hi-tensile steel. Plow is fully welded</b>
	Type, size and number of vertical reinforcement ribs.	<b>Eight (8) 1/2" flame cut ribs, ribs are 100% fully welded</b>
	Adjustable cutting edge angles to pavement measured from roadway surface through perpendicular back toward truck.	<b>Adjustable angles, 21 to 15 degrees</b>
	State number of hook up points from moldboard to frame.	<b>Four (4) (optional heavy duty push frame has six)</b>
	Type and size of reinforcement of frog at either end.	<b>3/4" x 4" x 4" lower angle, fully gusseted (carbide punched)</b>
	Type and size of circle frame	<b>A-Frame type, constructed with 1/2" x 3-1/2" x 3-1/2" channel</b>
	Size of double acting reversing cylinders.	<b>Two heavy duty 4" x 19" power reversing cylinders with 2" Nitrided rods. Cylinders are mounted above the push frame.</b>
	Size and type of reinforced snow flap	<b>3-ply, 1/2" thick x 12" wide</b>
	Type and size of push frame	<b>tubing</b>
	Carbide cutting Edge (AASHTO punched) size.	<b>5/8" x 8" x (length of plow) steel cutting edge is standard (see options for carbide)</b>
	Distance beyond vertical that snow deflectors integral with moldboard extends.	<b>28"</b>
	Size of Adjustable Snow Shoes	<b>None - See Options Includes adjustable parking stand</b>
	Weight of plow (less hitch and hydraulics)	<b>2,450 lbs.</b>
	Type and number of resettable HD compression spring trip mechanisms.	<b>Four (4) heavy duty adjustable moldboard trip springs, extension type, adjustable with hand tools, made of 9/16" wire.</b>
	Painting system with type of paint	<b>Primed &amp; Painted Std. Black (See options for different colors)</b>
	Warranty Information	<b>One Year Warranty, parts and labor</b>
	Volume Discounts	<b>N/A</b>
	<b>TOTAL PRICE:</b>	<b>\$ 11,346.00</b>
	Front Plow Options	
6.01	12' plow length in lieu of 11'	\$ 263.10
6.02	48" plow height in lieu of 43"	\$ 641.11

6.03	52" plow height in lieu of 43"	\$	1,636.60
6.04	Std. UTE Orange painted plow in lieu of std. black (All Plow Models & Sizes) (#IG4241040)	\$	173.97
6.05	Std. UTE Yellow painted plow in lieu of std. black (All Plow Models & Sizes) (#4421)	\$	517.61
6.06	Std. UTE Red painted plow in lieu of std. black (All Plow Models & Sizes) (#2303)	\$	644.33
6.07	Plow end markers, red cable type, 27", installed (set)	\$	105.24
6.08	Adjustable mushroom type shoes- std. pad, 12" round x 2" thick (installed with standard shoe brackets)	\$	1,711.77
6.09	Adjustable mushroom type shoes- Ni-Hard pad, 12" round x 2" thick (installed with standard shoe brackets)	\$	2,424.83
6.10	Adjustable shoes- Flat type shoe pad (installed with standard shoe brackets)	\$	1,704.25
6.11	Curb shoe, (2" cold rolled round), installed (each)	\$	182.56
6.12	Plow cutting edge shoe, installed (each)	\$	300.69
6.13	Trip cutting edge, one piece or split, in lieu of moldboard trip	\$	1,804.12
6.14	Moldboard trip/trip edge combo, in lieu of moldboard trip only	\$	2,991.84
6.15	Individually replaceable trip edge springs ilo standard	\$	665.81
6.16	3/4" x 6" carbide cutting edge with cover blade in lieu of std. (per ft.)	\$	106.31
6.17	Sabre Shielded Carbide cutting edge blades 3/4" x 6" ilo std. ("No" cover blade required) (per ft.)	\$	148.20
6.18	Flex Pro (Joma) cutting edge blades 3/4" x 6" ilo std. (Includes cover bar) (per ft.)	\$	177.19
6.19	Flex Pro (Joma) backer blades for additional support (per ft.)	\$	21.48
6.20	six main hinge points with the furthest hinge point extending about 11" from the end of the plow, in lieu of standard	\$	1,000.86
6.21	UTAW model has the same specs as standard UTA. The UTAW has a larger more finished off curl (bigger belly) and little more laid back cutting edge. This design helps to throw the snow better. Plow height is 46". (w/ 6" cutting edge) (NO TRIP CUTTING EDGE AVAILABLE ON THIS MODEL)	\$	413.45
6.22	1/2" Stucchi Multifaster coupler with parking station- installed (coupling under pressure)	\$	1,575.39
6.23	Plow portion of 29" Husting hitch in lieu of Loop Hitch	\$	1,600.09
6.24	Plow portion of 34" Husting hitch in lieu of Loop Hitch	\$	1,857.82
6.25	Roller Kit for 29" or 34" Husting hitch, installed on plow only	\$	667.96
6.26	Plow portion of Snap Link hitch in lieu of Loop Hitch	\$	845.15
6.27	Plow portion of Universal Pin hitch (Falls #46) in lieu of Loop Hitch	\$	201.89
6.28	Level lift assy. for Universal Pin hitch	\$	300.69
6.29	40" plow height w/ in lieu of 43" height (deduct)	\$	(344.72)
6.30	Mailbox/Guard rail corner cut (per side)	\$	451.03
6.31	Three piece trip cutting edge in lieu of std. 2-piece trip cutting edge	\$	208.33
6.32	UTE Frog Saver- Installed (helps prevent wearing into the lower angle) (Each)	\$	294.24
6.33	3/4" x 4" x 4" lower trip edge angle in lieu of std. 1/2" x 3" x 4"	\$	176.12
6.34	3/16" moldboard thickness in lieu of std. 10ga.	\$	429.55
	Cost per loaded mile for pickup and or delivery of vehicle (if applicable):	\$	5.60
	Delivery Starting Point City, State, & Zip:	N15921 Schubert Rd., Galesville, WI 54630	
	Body Shop Rate	\$	120.00
	Mechanic Shop Rate	\$	120.00

Price quote for:		6.0 NON MnDOT PRICE SCHEDULE - FRONT SNOW PLOW	
Vendor Name:	Universal Truck Equipment Inc.		
Contact Person:	Donnie Bjorge		
Street Address:	N15921 Schubert Rd.		
P.O. Box:			
City, State, Zip:	Galesville, WI 54630		
Phone #:	608-539-4600		
Toll Free #:			
Fax #:	608-539-4800		
Email Address:	donnie@universaltruckequipment.com		
	Information Requested	Answer	
	Plow Type (one way, reversable, high wing, v plow, etc)		
6.00	Two-Way Reversible Snow Plow - Make and Model	Universal CST-11-43L two way power reversible snow plow, moldboard trip type, 11' plow length. Note: plow portion of Loop hitch is standard (see options for other plow hitches).	
6.00	Moldboard Height	43" (measured with 6" cutting edge)	
	Moldboard Smoothed Rolled Design include Radius.	Multiple radius's 15 to 20	
	Discharge Height	43" (measured with 6" cutting edge)	
	Plow Throat depth from vertical to deepest point in.	14-1/2"	
	Moldboard thickness & type of steel	10ga. moldboard thickness, grade 50 Hi-tensile steel. Plow is fully welded	
	Type, size and number of vertical reinforcement ribs.	Eight (8) 1/2" flame cut ribs, ribs are 100% fully welded	
	Adjustable cutting edge angles to pavement measured from roadway surface through perpendicular back toward truck.	Adjustable angles, 20, 10 & 15 degrees	
	State number of hook up points from moldboard to frame.	Six (6)	
	Type and size of reinforcement of frog at either end.	3/4" x 4" x 4" lower angle, fully gusseted (carbide punched)	
	Type and size of circle frame	Semi-circle type, constructed with 1/2" x 3-1/2" x 3-1/2" rolled angle	
	Size of double acting reversing cylinders.	Two heavy duty 4" x 10" power reversing cylinders with 2" Nitrided rods. Cylinders are mounted above the push frame.	
	Size and type of reinforced snow flap	3-ply, 1/2" thick x 12" wide	
	Type and size of push frame	Push frame is constructed with 3/8" x 4" x 4" x 102" square tubing	
	Carbide cutting Edge (AASHTO punched) size.	carbide)	
	Distance beyond vertical that snow deflectors integral with moldboard extends.	27"	
	Size of Adjustable Snow Shoes	None - See Options Includes adjustable parking stand	
	Weight of plow (less hitch and hydraulics)	2,240 lbs.	
	Type and number of resettable HD compression spring trip mechanisms.	wire	
	Painting system with type of paint	Primed & Painted Std. Black (See options for different colors)	
	Warranty Information	One Year Warranty, parts and labor	
	Volume Discounts	N/A	
		TOTAL PRICE:	\$ 9,729.00
	Front Plow Options		
6.01	12' plow length in lieu of 11'	\$	263.10
6.02	48" plow height in lieu of 43"	\$	641.11
6.03	52" plow height in lieu of 43"	\$	1,636.60



6.04	Std. UTE Orange painted plow in lieu of std. black (All Plow Models & Sizes) (#G4241040)	\$	173.97
6.05	(#4421)	\$	517.61
6.06	Std. UTE Red painted plow in lieu of std. black (All Plow Models & Sizes) (#2303)	\$	644.33
6.07	Plow end markers, red cable type, 27", installed (set)	\$	105.24
6.08	Adjustable mushroom type shoes- std. pad, 12" round x 2" thick (installed with standard shoe brackets)	\$	1,711.77
6.09	Adjustable mushroom type shoes- Ni-Hard pad, 12" round x 2" thick (installed with standard shoe brackets)	\$	2,424.83
6.10	Adjustable shoes- Flat type shoe pad (installed with standard shoe brackets)	\$	1,704.25
6.11	Curb shoe, (2" cold rolled round), installed (each)	\$	182.56
6.12	Plow cutting edge shoe, installed (each)	\$	300.69
6.13	Trip cutting edge, one piece or split, in lieu of moldboard trip	\$	1,804.12
6.14	Moldboard trip/trip edge combo, in lieu of moldboard trip only	\$	2,991.84
6.15	Individually replaceable trip edge springs ilo standard	\$	665.81
6.16	3/4" x 6" carbide cutting edge with cover blade in lieu of std. (per ft.)	\$	106.31
6.17	Sabre Shielded Carbide cutting edge blades 3/4" x 6" ilo std. ("No" cover blade required) (per ft.)	\$	148.20
6.18	Flex Pro (Joma) cutting edge blades 3/4" x 6" ilo std. (Includes cover bar) (per ft.)	\$	177.19
6.19	Flex Pro (Joma) backer blades for additional support (per ft.)	\$	21.48
6.20	Stucchi Multifaster coupler with parking station (coupling under pressure)	\$	1,575.39
6.21	Plow portion of 29" Husting hitch in lieu of Loop Hitch	\$	1,600.09
6.22	Plow portion of 34" Husting hitch in lieu of Loop Hitch	\$	1,857.82
6.23	Roller Kit for 29" or 34" Husting hitch, installed on plow only	\$	667.96
6.24	Plow portion of Snap Link hitch in lieu of Loop Hitch	\$	845.15
6.25	Plow portion of Universal Pin hitch (Falls #46) in lieu of Loop Hitch	\$	201.89
6.26	Level lift assy. for Universal Pin hitch	\$	300.69
6.27	40" plow height w/ in lieu of 43" height (deduct)	\$	(344.72)
6.28	Mailbox/Guard rail corner cut (per side)	\$	451.03
6.29	Three piece trip cutting edge in lieu of std. 2-piece trip cutting edge	\$	208.33
6.30	UTE Frog Saver- Installed (helps prevent wearing into the lower angle) (Each)	\$	294.24
6.31	3/4" x 4" x 4" lower trip edge angle in lieu of std. 1/2" x 3" x 4"	\$	176.12
6.32	3/16" moldboard thickness in lieu of std. 10ga.	\$	429.55
6.33	Poly Moldboard Plow in lieu of steel moldboard (2-extra ribs/10 total)	\$	950.39
	Cost per loaded mile for pickup and or delivery of vehicle (if applicable):	\$	5.60
	Delivery Starting Point City, State, & Zip:	N15921 Schubert Rd., Galesville, WI 54630	
	Body Shop Rate	\$	120.00
	Mechanic Shop Rate	\$	120.00

Price quote for:	<b>6.0 NON MnDOT PRICE SCHEDULE - FRONT SNOW PLOW</b>	
Vendor Name:	<b>Universal Truck Equipment Inc.</b>	
Contact Person:	<b>Donnie Bjorge</b>	
Street Address:	<b>N15921 Schubert Rd.</b>	
P.O. Box:		
City, State, Zip:	<b>Galesville, WI 54630</b>	
Phone #:	<b>608-539-4600</b>	
Toll Free #:		
Fax #:	<b>608-539-4800</b>	
Email Address:	<b>donnie@universaltruckequipment.com</b>	
	<b>Information Requested</b>	<b>Answer</b>
	Plow Type ( one way, reversable, high wing, v plow, etc)	
6.00	Two-Way Reversible Snow Plow - Make and Model	<b>Universal - UTAGW-12-58L Gull Wing High Speed Plow - moldboard trip type 12' plow length. Note: plow portion of loop hitch is standard (see options for other plow hitches).</b>
6.00	Moldboard Height	<b>45" (measured with 6" cutting edge)</b>
	Moldboard Smoothed Rolled Design include Radius.	<b>Multiple radius's 15 to 20</b>
	Discharge Height	<b>58" (measured with 6" cutting edge)</b>
	Plow Throat depth from vertical to deepest point in.	<b>25"</b>
	Moldboard thickness & type of steel	<b>3/16" thick, grade 50 Hi-tensile steel. Plow is fully welded</b>
	Type, size and number of vertical reinforcement ribs.	<b>Eight (8) 1/2" flame cut ribs, ribs are 100% fully welded</b>
	Adjustable cutting edge angles to pavement measured from roadway surface through perpendicular back toward truck.	<b>15 degrees to 30 degrees</b>
	State number of hook up points from moldboard to frame.	<b>Six (6)</b>
	Type and size of reinforcement of frog at either end.	<b>3/4" x 4" x 4" lower angle, fully gusseted (carbide punched)</b>
	Type and size of circle frame	<b>A-Frame type, constructed with 1/2" x 3-1/2" x 3-1/2" channel</b>
	Size of double acting reversing cylinders.	<b>Two heavy duty 4" x 19" power reversing cylinders with 2" Nitrided rods. Cylinders are mounted above the push frame.</b>
	Size and type of reinforced snow flap	<b>3-ply, 1/2" thick x 12" wide</b>
	Type and size of push frame	<b>Push frame is constructed with 3/8" x 4" x 4" x 117" square tubing</b>
	Carbide cutting Edge (AASHTO punched) size.	<b>5/8" x 8" x (length of plow) steel cutting edge is standard (see options for carbide)</b>
	Distance beyond vertical that snow deflectors integral with moldboard extends.	<b>28"</b>
	Size of Adjustable Snow Shoes	<b>None - See Options Includes adjustable parking stand</b>
	Weight of plow (less hitch and hydraulics)	<b>2,450 lbs.</b>
	Type and number of resettable HD compression spring trip mechanisms.	<b>extension type, adjustable with hand tools, made of 9/16" wire.</b>
	Painting system with type of paint	<b>Primed &amp; Painted Std. Black (See options for different colors)</b>
	Warranty Information	<b>One Year Warranty, parts and labor</b>

	Volume Discounts	N/A
		<b>TOTAL PRICE: \$ 16,039.00</b>
	Front Plow Options	
6.01	11' plow length in lieu of 12' (deduct)	\$ (601.37)
6.02	Std. UTE Orange painted plow in lieu of std. black (All Plow Models & Sizes) (#IG4241040)	\$ 173.97
6.03	Std. UTE Yellow painted plow in lieu of std. black (All Plow Models & Sizes) (#4421)	\$ 517.61
6.04	Std. UTE Red painted plow in lieu of std. black (All Plow Models & Sizes) (#2303)	\$ 644.33
6.05	Plow end markers, red cable type, 27", installed (set)	\$ 105.24
6.06	Adjustable mushroom type shoes- std. pad, 12" round x 2" thick (installed with standard shoe brackets)	\$ 1,711.77
6.07	Adjustable mushroom type shoes- Ni-Hard pad, 12" round x 2" thick (installed with standard shoe brackets)	\$ 2,424.83
6.08	Adjustable shoes- Flat type shoe pad (installed with standard shoe brackets)	\$ 1,704.25
6.09	Curb shoe, (2" cold rolled round), installed (each)	\$ 182.56
6.10	Trip cutting edge, one piece or split, in lieu of moldboard trip	\$ 1,804.12
6.11	Three piece trip cutting edge in lieu of std. 2-piece trip cutting edge	\$ 208.33
6.12	Moldboard trip/trip edge combo, in lieu of moldboard trip only	\$ 2,991.84
6.13	Individually replaceable trip edge springs ilo standard	\$ 665.81
6.14	3/4" x 6" carbide cutting edge with cover blade in lieu of std. (per ft.)	\$ 106.31
6.15	ft.)	\$ 148.20
6.16	Flex Pro (Joma) cutting edge blades 3/4" x 6" ilo std. (Includes cover bar) (per ft.)	\$ 177.19
6.17	Flex Pro (Joma) backer blades for additional support (per ft.)	\$ 21.48
6.18	1/2" Stucchi Multifaster coupler with parking station- installed (coupling under pressure)	\$ 1,575.39
6.19	Plow portion of 29" Husting hitch in lieu of Loop Hitch	\$ 1,600.09
6.2	Plow portion of 34" Husting hitch in lieu of Loop Hitch	\$ 1,857.82
6.21	Roller Kit for 29" or 34" Husting hitch, installed on plow only	\$ 667.96
6.22	Plow portion of Snap Link hitch in lieu of Loop Hitch	\$ 845.15
6.23	Plow portion of Universal Pin hitch (Falls #46) in lieu of Loop Hitch	\$ 201.89
6.24	Level lift assy. for Universal Pin hitch	\$ 300.69
6.25	Mailbox/Guard rail corner cut (per side)	\$ 515.46
6.26	UTE Frog Saver- Installed (helps prevent wearing into the lower angle) (Each)	\$ 294.24
6.27	3/4" x 4" x 4" lower trip edge angle in lieu of std. 1/2" x 3" x 4"	\$ 176.12
	Cost per loaded mile for pickup and or delivery of vehicle (if applicable):	\$ 5.60
	Delivery Starting Point City, State, & Zip:	N15921 Schubert Rd., Galesville, WI 54630
	Body Shop Rate	\$ 120.00
	Mechanic Shop Rate	\$ 120.00