

FD. PT. H4P  
240/480 VOLT

FD. PT. H4P

FD. PT. H4P

LIGHTING STANDARDS AND BASES

NO.	STATION	LT. RT.	LOCATION	TYPE
(2) 1	30+082	-	T.H. 100 S.B.	BB-12
2	30+005	-	T.H. 100 S.B.	4-12
(2) 3	29+928	-	T.H. 100 S.B.	BB-12
(2) 4	29+855	-	T.H. 100 S.B.	BB-12
(2) 5	29+780	-	T.H. 100 S.B.	BB-12
(2) 6	29+703	-	T.H. 100 S.B.	BB-12
(2) 7	29+628	-	T.H. 100 S.B.	BB-12
8	29+555	-	T.H. 100 S.B.	4-12
9	29+485	-	T.H. 100 S.B.	4-12
10	29+410	-	T.H. 100 S.B.	4-12
(2) 11	29+330	-	T.H. 100 S.B.	BB-12
(2) 12	16+313	-	RAMP A	3B-12
13	16+235	-	RAMP A	3-12
14	13+115	-	RAMP A-1	3-12

LIGHTING STANDARDS AND BASES

NO.	STATION	LT. RT.	LOCATION	TYPE
15	6+420	-	RAMP D	3-12
16	5+086	-	RAMP D-1	3-12
17	6+300	-	RAMP D	3-12
(2) 18	6+230	-	RAMP D	3B-12
(2) 19	6+157	-	RAMP D	3B-12
(2) 20	6+090	-	RAMP D	3B-12
21	13+041	-	RAMP A-1	4-12
22	52+424	-	T.H. 55 W.B.	L4-12
23	52+351	-	T.H. 55 W.B.	L4-12
24	52+356	-	T.H. 55 E.B.	L4-12
25	52+429	-	T.H. 55 E.B.	L4-12
26	5+515	-	RAMP D-1	4-12
27	52+570	-	T.H. 55 E.B.	L.L
28	52+585	-	T.H. 55 E.B.	L.L

(2) ANCHORAGE PROVIDED IN TYPE F BARRIER OR BRIDGE PLAN  
SEE SHEET NO. 1 FOR PLACEMENT OF LIGHTING UNITS TYPE 3-12 & 4-12

B AND R DENOTE CURRENT CARRYING CONDUCTORS  
W DENOTES NEUTRAL CONDUCTOR

PAD MOUNTED SOURCE OF POWER  
SERVICE CABINET SECONDARY TYPE L1.  
FD. PT. H4P, 240/480 V. (METERED)  
EQUIPMENT PAD A REQUIRED

PAD MOUNTED SOURCE OF POWER  
SERVICE CABINET SECONDARY TYPE L1.  
FD. PT. H4N, 240/480 V. (METERED)  
EQUIPMENT PAD INSTALLED IN SIGNAL PLAN

FD. PT. H4N

LIGHTING STANDARDS AND BASES

NO.	STATION	LT. RT.	LOCATION	TYPE
(2) 1	29+290	-	T.H. 100 N.B.	BB-12
(2) 2	29+365	-	T.H. 100 N.B.	BB-12
(2) 3	29+430	-	T.H. 100 N.B.	BB-12
(2) 4	29+512	-	T.H. 100 N.B.	BB-12
(2) 5	29+595	-	T.H. 100 N.B.	BB-12
(2) 6	29+672	-	T.H. 100 N.B.	BB-12
(2) 7	29+752	-	T.H. 100 N.B.	BB-12
(2) 8	29+832	-	T.H. 100 N.B.	BB-12
(2) 9	29+913	-	T.H. 100 N.B.	BB-12
(2) 10	29+992	-	T.H. 100 N.B.	BB-12
(2) 11	30+072	-	T.H. 100 N.B.	BB-12
(2) 12	8+065	-	RAMP C	3B-12
(2) 13	8+138	-	RAMP C	3B-12
14	7+031	-	RAMP C-1	4-12


FD. PT. H4N

LIGHTING STANDARDS AND BASES

NO.	STATION	LT. RT.	LOCATION	TYPE
15	9+070	-	RAMP B	3-12
16	9+115	-	RAMP B	3-12
17	9+185	-	RAMP B	3-12
(2) 18	9+257	-	RAMP B	3B-12
(2) 19	9+328	-	RAMP B	3B-12
(2) 20	9+387	-	RAMP B	3B-12
21	52+789	-	T.H. 55 W.B.	L4-12
22	52+716	-	T.H. 55 W.B.	L4-12
23	52+643	-	T.H. 55 W.B.	L4-12
24	52+580	-	T.H. 55 W.B.	L.L
25	52+564	-	T.H. 55 W.B.	L.L
26	52+655	-	T.H. 55 E.B.	L4-12
27	52+728	-	T.H. 55 E.B.	L4-12
28	52+801	-	T.H. 55 E.B.	L4-12

(2) ANCHORAGE PROVIDED IN TYPE F BARRIER OR BRIDGE PLAN  
SEE SHEET NO. 1 FOR PLACEMENT OF LIGHTING UNITS TYPE 3-12 & 4-12

AS-BUILT 09/2010



LIGHTING PLAN

CERTIFIED BY *Shawn J. Lodal* REG. NO. 21180  
PROFESSIONAL ENGINEER

STATE PROJ. NO. 2735-134 (T.H. 100)

SHEET NO. 887 OF 1118 SHEETS