



FD. PT. S5E

LIGHTING STANDARDS AND BASES

NO.	STATION	LT.	RT.	LOCATION	TYPE	WALL - WALL STATION
(4)	1		-	T.H. 494 EBL	6B-49	RWALLA - 15+66.97
(4)	2		-	T.H. 494 EBL	6B-49	RWALLB - 18+36.55
(4)	3		-	T.H. 494 EBL	6B-49	RWALLB - 21+06.12
(4)	4		-	T.H. 494 EBL	6B-49	RWALLB - 23+75.92
(1)(2)	5	70'		T.H. 494 EBL	3-100	
(1)(2)	6	70'		T.H. 494 WBL	3-100	
(1)(2)	7	70'		T.H. 494 WBL	3-100	
(1)(2)	8	40'		T.H. 494 WBL	3-100	
(4)	9		-	T.H. 494 WBL	6B-49	RWALLC1 - 23+09.67
(4)	10		-	T.H. 494 WBL	6B-49	RWALLC1 - 20+39.35
(4)	11		-	T.H. 494 WBL	6B-49	RWALLC - 14+07.06
(4)	12		-	T.H. 494 WBL	6B-49	RWALLC - 11+35.71

(1) INSTALL SALVAGED HIGH MAST LIGHT STANDARD ON NEW FOUNDATION AND F. & I. 1000 WATT HIGH PRESSURE SODIUM LUMINAIRES

(2) SHIELD HOUSE SIDE

(4) LIGHT ANCHORAGE IN RETAINING WALL