



- NOTES:**
- 1. CULVERT MARKERS SHOULD BE PLACED ON THE SIDE OF THE CULVERT NEAREST THE APPROACHING TRAFFIC OF THE ROADWAY ON WHICH THE CULVERT IS LOCATED.
  - 2. THE SYMBOL X ON THE DRAWING INDICATES THE PROPER LOCATION OF THE MARKER.
  - 3. OPTIONAL FLEXIBLE POST MAY BE GRAY OR YELLOW WITH THE TOP 12" COVERED WITH BLACK NON-REFLECTIVE MATERIAL. THE GRAY OPTIONAL FLEXIBLE POST MAY HAVE THE TOP 12" INCHES COVERED WITH YELLOW VIP SHEETING.
  - 4. EMBEDMENT FOR THE OPTIONAL FLEXIBLE POST SHALL BE AS SPECIFIED BY THE MANUFACTURER.

APPROVED           MAY 3, 2004            
  
 STATE DESIGN ENGINEER

STATE OF MINNESOTA  
 DEPARTMENT OF TRANSPORTATION  
 INSTALLATION OF CULVERT MARKERS

SPECIFICATION REFERENCE  
 2554

STANDARD PLATE NO.  
 8150C

U CHANNEL POST SHALL CONFORM TO SPEC. 3401 AND HAVE A NOMINAL WEIGHT OF 2 LBS. PER FT. AND SHALL BE GALVANIZED ACCORDING TO ASTM A 123.  
 BOLT HOLES WILL NOT BE REQUIRED BUT WILL BE ACCEPTABLE IN THE POST.

MARKER POST INSTALLATION ①